


SACC-MINFR-5CON-PG 9

Order No.: 1521517



Sensor/actuator connector, female, angled, 5-pos., 7-8", screw connection, metal knurl, cable screw connection PG 9

Commercial data	
EAN	 4 017918 949730
Pack	1
Customs tariff	85369010
Catalog page information	Page 53 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-03-22



Technical data

General data	
Rated current at 40°C	9 A
Rated voltage	250 V
Number of positions	5
Volume resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Ambient temperature (operation)	-25 °C ... 85 °C (Male connector / female connector)

General characteristics

Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR / PA66
Material of grip body	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Type of connection	Screw connection
Conductor cross section stranded min.	0.34 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	22
Conductor cross section AWG/kcmil max	16
External cable diameter	6 mm ... 8 mm
Status display	No

Certificates




Certification

CUL, UL


Drawings

Functional drawing



Dimensioned drawing

Female 7/8"-16UNF, angled, Pg9



Schematic diagram

Pin assignment, socket, 7/8"-16UNF, 5-pos., view of female side

