



### Model Number


**V3S-GM-5M-PUR**

Cable connector, M8, 3-pin, PUR cable

### Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Halogen-free
- Suitable for 2- and 3-wire technology

### Dimensions



### Technical data

#### General specifications

Number of poles	3
Connection 1	Connector, male
Construction type 1	straight
Threading 1	M8
Connection 2	free cable end

#### Electrical specifications

Operating voltage	max. 60 V DC
Test voltage	> 1500 V <sub>eff</sub> AC
Operating current	max. 4 A
Volume resistance	< 5 mΩ

#### Ambient conditions

Ambient temperature	-25 ... 100 °C (248 ... 373 K) for temperatures over 80 °C (353 K) reduced elongation at tear
Degree of soiling	3

#### Mechanical specifications

Contact elements	spring-loaded contact socket
pin diameter	1 mm
Protection degree	IP67
Material	
Contacts	CuSn / Au
Contact surface	Au
Handle	TPU, green
Cable	PUR
(Cap??-translator) connector	diecast zinc
Core isolation	PP
Cable	
Sheath diameter	Ø4.8 mm
Bend radius	> 10 x conductor diameter, appropriate for conveyor chains
Colour	grey
Cores	3 x 0.34 mm <sup>2</sup>
Conductor construction	19 x 0.15 mm Ø
Length	L 2 m
Flammability	
Contact material	94V-2
Housing	94V-2

### Electrical connection 1

